


SMD Seam Sealing Crystals

3.2x2.5x0.7mm S32 Series



Features

- High precision and high frequency stability.
- Extremely good for reducing EMI effect.
- The best choice of Bluetooth , Wi-Fi and other short range wireless communication.
- RoHS Compliant / Pb Free.



Crystals specifications

ITEMS/TYPE	S32
Frequency Range	8~64MHz
Load Capacitance	8pF, 10pF, 12pF, or specify
Frequency Tolerance (at 25°C)	±10ppm, ±20ppm, or specify
Frequency Stability Over Operating Temperature Range	±10ppm, ±20ppm, or specify
Operating Temperature Range	-40~+85°C, or specify
Shunt Capacitance (C0)	3pF Max.
Drive Level	1~200μW (100μW typical)
Aging (at 25°C)	± 3 ppm/year Max.
Storage Temperature Range	-40~+125°C

Equivalent Series Resistance(ESR)

Frequency Range	Mode	ESR.	Frequency Range	Mode	ESR.
8.000~9.999MHz	FAT,Fundl	300 ΩMax.	20.000~29.999MHz	uAT,Fundl	60 ΩMax
10.000~11.999MHz	uAT,Fundl	120 ΩMax.	30.000~39.999MHz	uAT,Fundl	40 ΩMax
12.000~15.999MHz	uAT,Fundl	100 ΩMax.	40.000~64.000MHz	uAT,Fundl	30 ΩMax
16.000~19.999MHz	uAT,Fundl	80 ΩMax.			

Dimensions and patterns(unit:mm)

